GAOKEview®

# Product Specification

**Product Name: 32 inch Mobile Smart Screen**
**Model: GK-3202A**



***All information in this document is subject to the final interpretation of the manufacturer, all unauthorised and unauthorised copying is not recognised and should be prohibited.**
**This document may not fully reflect all the latest changes in the product, the actual product shall prev**

# Product Specification Version Log

| Version | Date | Author | Description |
|---|---|---|---|
| V1.0 | 08-06-2026 | Homer Ni | Initial release |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

## Function

- HD ten-point capacitive touch LCD
- Rotate vertically at 90°, automatic switch between landscape and portrait mode.
- Adjustable pitching angle.
- Simple tablet operation display interface.
- Wireless screen projection.
- High-quality stereo speakers, output power can reach 2x8W.
- Built-in 8-megapixel camera, two analog MIC and Ambient Light Sensor.
- Bases with omni-directional wheels, move much easier.
- Android14 OS.
- Support HDMI, Type-C, USB3.0 HD video interfaces.
- Built-in high-performance dual-frequency WIFI antenna, support WIFI6+BT5.2 high-speed communication.

## Display

| | |
|---|---|
| Size | 32 inch |
| Brand | GAOKEview |
| Backlight Type | ELED |
| Resolution(pixels) | 3840x2160(pixels) |
| Brightness | 250nit(Typ) |
| Contrast Ratio | 3000：1(Typ) |
| Response Time | 16ms(Typ)/22(Max) |
| Pixel Pitch(mm) | 0.06053(H)x0.18159(W) |
| Refreshing Frequency | 60Hz |
| Life Time | 30,000 hrs (min.) |
| Color Gamut(X%NTSC) | 90%(Typ)85%(Min) |
| View Area(mm) | 697.3056*392.2344mm |
| Display Colors | 1.07 Billion colors |

## Electrica

| | | |
|---|---|---|
| Chipset | | RK3576D |
| CPU | Architecture | ARM Cortex-A72*4+ARM Cortex-A53*4 |
| | Working Frequency | ARM Cortex-A72:2.2GHz<br>ARM Cortex-A53:2.0GHz |
| | Core | Octa-core |
| GPU | | Mali-G52 MC3 |
| RAM | | 8GB |
| ROM | | Standard:64GB, Optional:128GB |
| OS | | Android 14 |
| Power Supply | | 90W ， 19V/4.74A |
| Batteries | | 8550mAh/11.1V |
| Audio Output Power | | 2x8W/4Ω |
| Charging time of the entire battery(8550mAh/11.1V) | | 3.17H |
| Battery life of the whole machine(8550mAh/11.1V) | | 3.27H |

## Mainboard Interface

| | |
|---|---|
| HDMI* 1 | Max Resolution: 2160P@60Hz<br>Edition：HDMI 2.0 |
| Type-C*1 | Type-C screen mirroring supported; plays images, music and videos. 10W (5V/2A) output power |
| USB3.0* 1 | USB support images, music, video file play |

## WIFI

| | |
|---|---|
| Operating Frequency | 2.4GHz/5GHz |
| WI-FI Standard | 802. 11a/b/g/n/ac/ax |
| Bluetooth | 2. 1+EDR/4.2/5.2 |

## TOUCH

| | |
|---|---|
| Support ten-point capacitive touch | |
| Camera | 8-megapixel |
| Array microphones | 2-channel analog silicon microphones |

## Structure

| | |
|---|---|
| **Product Size(W x D x H)** | **734x429x55mm(no chassis)** |
| | **734x426x1331mm(with metal bracket)** |
| **Package Size(W x D x H)** | **1013×250×530mm** |
| **Housing Material** | **PC+ABS** |

## Accessories

| | |
|---|---|
| **Certificate of conformity** | **x1** |
| **specification** | **x1** |
| **Warranty card** | **x1** |
| **adapter** | **x1** |
| **Universal wheel base** | **x1** |
| **Connecting rod** | **x1** |
| **Screws** | **x4** |
| **Remote control (Optional)** | **×1** |

## Environment

- **Operating temperature 0℃ ~ + 40℃**
- **Charging temperature 0℃ ~ +40℃**
- **Storage temperature -10℃ ~ +50℃ .**
- **Operating humidity 0% ~ 65% RH Non-Condensing**
- **Storage humidity 0% ~ 80% RH Non-Condensing**
- **Operating altitude ⩽3000m**

**Hangzhou Gaoke Industry&Trade Co.,Ltd.(1992-2026)**

Add: Building A6, Phase I,Cainiao Zhigu Industrial Park, No.2-150 Yunlian Road, Yuhang District, Hangzhou, China

Tel: +86 571 8998 6945

Web: www.hzgaokegroup.com